







More information please login www.dinggaojx.cn www.sxdinggao.en.alibaba.com



## PRODUCT DESCRIPTION

- Beam using high strength H steel .
- Platform overall molding, bearing up to 6.5 tons .
- Manual mechanical reset insurance mechanism .Safety,reliable and high efficiency synchronization.
- Export-type pneumatic safety components have long service life and high synchronization efficiency.
- · Standard oil-water separator with pressure gauge.
- The wire rope fracture protective mechanism can effectively prevent the cable drop fast when fracture.
- Optional slide plate for four-wheel alignment.
- Optional hydraulic rolling jack, bearing 7000 pounds(3.2tons), convenient adjustment of the chassis and disassembling tyres.
- Yellow warning parts on the slope, at the same time of warning also protect the ground friction.
- Four columns secure level accurate adjustable.
- · All moving parts are equipped with grease nipple ,convenient to fill lubricating oil.
- Suitable for 4s, middle and top grade auto maintenance companies.




















## **Technical parameters**

Model	YH-6.5
_xWxH	7040x3575x2254mm
Lifting Height	1850mm
Lifting Time	50s
Length of Columns	5430mm
Overall Length	7040mm
Inside Soleplate of Columns Width	2655mm
Overall Width	3575mm
Platform Length	5770mm
Lifting Capacity	6500kg
Runway Width	508mm
Width Between Runway	1078-1178mm
Packing Size	6010x570x900mm
Gross Weight	1800kg



## Detail















Active plate can fit for different Air cylinder for air relese. size tumtable.


Nylon slide board for limit insurance piece.

Structure of cable and pulley Slide plate for wheel alignment. Optional rolling jack. under main runway.

SHAOXING DINGGAO MECHANICAL EQUIPMENT CO., LTD.

Oil cylinder with explosionproof valve.





NO.186 Mashan Road. Paojiang Industrial Zone. Shaoxing. Zhejiang.China TEL: 0086-0575-84623366 FAX: 0086-0575-84623331 E-mail: lichao@dinggaomechanical.com



