









YH-4.0B **FOUR POST LIFT** 

> More information please login www.dinggaojx.cn www.sxdinggao.en.alibaba.com

## PRODUCT DESCRIPTION

- · Beam using high strength rectangular tube with beautiful appearance.
- Platform overall molding, bearing up to 4 tons .
- Manual mechanical reset insurance mechanism .Safety, reliable and high efficiency synchronization.
- The cable fracture protective mechanism can effectively prevent the cable drop fast when fracture.
- · Optional slide plate for four-wheel alignment.
- Optional hydraulic rolling jack, bearing 4500 lbs(2 tons), lifting height 330mm, and there is hose bracket on the column.
- · Yellow warning parts on the up ramp, at the same time of warning also protect the ground friction.
- Four columns secure level accurate adjustable.
- There is a throttle valve on the channel for oiling.
- · All moving parts are equipped with grease nipple ,convenient to fill lubricating oil efficiency.











Model	YH-4.0B
xWxH	5645x3436x2222mm
ifting Height	1850mm
Lifting Time	50s
Length of Columns	4290mm
Overall Length	5645mm
Inside Soleplate of Columns Width	2546mm
Overall Width	3436mm
Platform Length	4600mm
Lifting Capacity	4000kg
Runway Width	508mm
Width Between Runway	1000mm-1100mm
Packing Size	4750x570x725mm
Gross Weight	1140kg



## Detail







Oil cylinder with explosion-proof Insurance piece in side the column. Up ramp with yellow slider can valve. Up ramp with yellow slider can warn people and protect friction.





warn people and protect friction. rolling jack.



The valve control platform and



Optional rolling jack.





## SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO.,LTD.

NO.186 Mashan Road. Paojiang Industrial Zone. Shaoxing. Zhejiang.China TEL: 0086-0575-84623366 FAX: 0086-0575-84623331 E-mail: lichao@dinggaomechanical.com



