







More information please login www.dinggaojx.cn www.sxdinggao.en.alibaba.com

PRODUCT DESCRIPTION

- · Beam using high strength rectangular tube with beautiful appearance.
- · Platform overall molding, bearing up to 3.5 tons .
- · Automatic rest type pneumatic safety valve .Safety,reliable and high efficiency synchronization.
- · Standard oil-water separator with pressure gauge.
- The wire rope fracture protective mechanism can effectively prevent the cable drop fast when fracture.
- · Optional slide plate for four-wheel alignment.
- . Optional hydraulic rolling jack, bearing 4500 lbs(2 tons), lifting height 330mm, and there is hose bracket on the column.
- Yellow warning parts on the slope, at the same time of warning also protect the ground friction.
- · Four columns secure level accurate adjustable.
- There is a throttle valve on the channel for oiling.
- All moving parts are equipped with grease nipple ,convenient to fill lubricating oil.
- · Export-type pneumatic safety components have long service life and high synchronization efficiency.




















Technical parameters	
Model	YH-3.5T
LxWxH	5127.5x3555x2216mm
Lifting Height	1950mm
Lifting Time	50s
Length of Columns	4030mm
Overall Length	5127.5mm
Inside Soleplate of Columns Width	2785mm
Overall Width	3555mm
Platform Length	4300mm
Lifting Capacity	3500kg
Runway Width	480mm
Width Between Runway	1000mm
Packing Size	4400x570x800mm
Gross Weight	960kg





Detail







with explosion-proof valve.



under main runway.



Active plate can fit for different size tumtable.



Slide plate for wheel alignment. Optional rolling jack.







SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO.,LTD.







More information please login: www.dinggaojx.cn www.sxdinggao.en.alibaba.com