









More information please login www.dinggaojx.cn www.sxdinggao.en.alibaba.com

PRODUCT DESCRIPTION

- · Vertical rise and fall parking lift, It is the ideal equipment for weight within 9000 lbs vehicle parking, Lifting height 2150mm, Lifting capacity 9000 lbs.
- Convenient installation, compact structure, the special mobile fitting make the whole device move convenient when no-load.
- Manual mechanical safety organ and cable fracture protective mechanism, double safety mechanism, more safety.
- It use high density slide blocks in the columns,Long service life.
- Explosion-proof throttle valve on the oil tube, It can prevent falling fast because of oil tube burst.
- The platform is made of high strength antiskid pattern plate overall molding.
- · The special brake block can prevent the vehicles moving.
- · Optional rolling jack, convenient for maintenance vehicles.


















Technical parameters Model PP-9 LxWxH 5782.5x3354x2456mm Lifting Height 2150mm Lifting Time 50s Length of Columns 4693mm Overall Length 5782.5mm Inside Soleplate of Columns Width 2484mm Overall Width 3354mm Platform Length 4990mm Lifting Capacity (9000lbs)4000kg Runway Width 508mm Width Between Runway 994mm Packing Size 5170x570x725mm



Detail

Gross Weight



Cable and pulley under main platform. Caster kit can make people



move lift easy when no-load.



1120kg

Manual safety bar for release.



Up ramp with yellow slider can warn people and protect friction.



Safety mechanism for protect quickly declined cause by cable breakage.



Nylon slide board for limit insurance





SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO.,LTD.







www.dinggaojx.cn www.sxdinggao.en.alibaba.com